

# HD Color Video Camera (Pan/Tilt)

Model No.: HD 652

720p/1080p USB interface



Low Cost High Performance 2.0 Megapixel HD Color Video camera achieved 1080p@30 or 720p@30 high quality images. Equipped with 4mm fixed lens with 72.5 degree wide Horizontal View angle, USB 2.0 ideally for Web conferencing system, easily connecting to laptop for whom on business trip.

## Features:

- ⊗ Smart design High Definition PTZ camera
- ⊗ Fast and smooth video handling
- ⊗ Low cost design for video conferencing
- ⊗ Work & Standby LED indicator
- ⊗ Speed Match
- ⊗ Auto/Manual IRIS/brightness/WB
- ⊗ RS-232C/VISCA Protocol
- ⊗ Boundary scanning
- ⊗ Image auto-flip
- ⊗ OSD Menu on screen
- ⊗ USB 2.0 simple connection for PTZ Control & video display

## Performance:

- ⊗ 1920x1080pixels progressive @30fps
- ⊗ 4 mm fixed lens
- ⊗ HOV 72.5 degree
- ⊗ 1/2.7" HD color CMOS
- ⊗ Pan ±180degree continuously
- ⊗ Tilt + 90 degree, - 45 degree
- ⊗ 64 preset positions
- ⊗ 4 cruise lines
- ⊗ DC 12V, 1.2A

## Dimension:

- ⊗ L 124mm x W 120mm x H145mm
- ⊗ N. Weight: 1.3kgs
- ⊗ G. Weight: 1.5kgs

## Installation:

- ⊗ Desktop
- ⊗ Ceiling/wall mount
- ⊗ Standard Tripod accessory
- ⊗ 5 meters USB Cable

## Multi-interface rear image



## Bottom board



**Specification sheet**

Image SenSor	Sensor	1/2.7" HD color CMOS
	Signal System	PAL/NTSC
	Minimum Scene Illumination	0.5Lux at F2.0
	White Balance	AUTO/Manual
	Gain Control	AUTO
	Back-light compensation	ON/OFF
	S/N Ratio	>50db
Lens	Lens	4 mm
	Iris	AUTO/Manual
	Zoom	Fixed lens
	Hov	72.5 degree
Video Output	USB Interface	
Video format	1080p@30, 720p@30	
Control Decoder	EIA/RS-485, USB	
Communication	EIA/RS-232 ( Bidirectional )	
PTZ Control Protocol	VISCA, PELCO-D	
Baud Rate	9600/38400bps	
Patrol tours	4	
Preset	64	
Save status after Power off	Support	
Speed Matching Function	Support	
Image Auto Flip	Support	
Pan Speed	0-280 degrees/s	
Tilt Speed	0-100 degrees/s	
Pan Rotation Angle	360 degrees	
Tilt Rotation Angle	+ 90 degrees, - 45 degree	
Auto Pan Scan	Support	
Boundary Scan	0-359 degree ( Programmable )	
Remoter Control	IR Wireless remote control P/T/Z	
Power	DC12V ±10% 1.2A	
Operation Temperature	0℃ ~ 50℃	
Environmental humidity	0-95%RH(non-condensaion)	
Length X width X high	124x120x145mm/220x175x220mm(NET/PACKAGE)	
Weight	640g/1100g(NET/PACKAGE)	

## Accessories kits in package:

1x HD Color Video Camera  
 1x DC 12V/2A Power Adaptor  
 1x User's manual

1x Installation brackets & screws  
 1x RS 232 Control Cable  
 1x 5meters USB Cable

1x IR Remote Controller




## Installation

**Ceiling mount**



**Wall mount**



**Wall mount**

